

# **Vintessential Laboratories**

Chemwatch: **32-7640** Version No: **4.1** Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements Chemwatch Hazard Alert Code: 1

Issue Date: **11/01/2019** Print Date: **10/12/2022** L.GHS.AUS.EN.E

#### SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier			
Product name	D-Gluconic Acid Analysis Kit - Vial 4		
Chemical Name	Not Applicable		
Synonyms	Not Available		
Chemical formula	Not Applicable		
Other means of identification	Not Available		

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Laboratory reagent.

#### Details of the manufacturer or supplier of the safety data sheet

Registered company name	Vintessential Laboratories		
Address	32 BRASSER AVENUE DROMANA VIC 3936 Australia		
Telephone	+61 3 5987 2242		
Fax	+61 3 5987 3303		
Website	Not Available		
Email	Not Available		

#### Emergency telephone number

Association / Organisation	Poisons Information Centre
Emergency telephone numbers	13 11 26
Other emergency telephone numbers	Not Available

### **SECTION 2 Hazards identification**

Classification of the substance or mixture			
Poisons Schedule	Not Applicable		
Classification [1]	Not Applicable		
Label elements			
Hazard pictogram(s)	Not Applicable		
Signal word	Not Applicable		

#### Hazard statement(s)

Not Applicable

### Precautionary statement(s) Prevention Not Applicable

Precautionary statement(s) Response

#### Not Applicable

Precautionary statement(s) Storage

### Not Applicable

Precautionary statement(s) Disposal

Not Applicable

# **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

### Mixtures

CAS No	%[weight]	Name	
Not Available	100	ingredients determined not to be hazardous	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

### **SECTION 4 First aid measures**

Description of first aid measur	es
Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<ul> <li>If skin contact occurs:</li> <li>Immediately remove all contaminated clothing, including footwear.</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5 Firefighting measures**

### Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

### Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
rice for firefighters	
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> <li>DO NOT approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> <li>Equipment should be thoroughly decontaminated after use.</li> </ul>
Fire/Explosion Hazard	<ul> <li>The material is not readily combustible under normal conditions.</li> <li>However, it will break down under fire conditions and the organic component may burn.</li> <li>Not considered to be a significant fire risk.</li> <li>Heat may cause expansion or decomposition with violent rupture of containers.</li> <li>Decomposes on heating and may produce toxic fumes of carbon monoxide (CO).</li> <li>May emit acrid smoke.</li> <li>Combustion products include: carbon dioxide (CO2) nitrogen oxides (NOx) sulfur oxides (SOx) other pyrolysis products typical of burning organic material. May emit corrosive fumes.</li> </ul>
HAZCHEM	Not Applicable

### **SECTION 6 Accidental release measures**

Personal precautions, protective equipment and emergency procedures

# See section 8

### **Environmental precautions**

See section 12

### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Wipe up.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours/ aerosols or dusts and avoid contact with skin and eyes.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>
Major Spills	<ul> <li>Clean up all spills immediately.</li> <li>Secure load if safe to do so.</li> <li>Bundle/collect recoverable product.</li> <li>Collect remaining material in containers with covers for disposal.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

Precautions for safe handling	
Safe handling	<ul> <li>DO NOT allow clothing wet with material to stay in contact with skin</li> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Avoid contact with moisture.</li> <li>Avoid contact with incompatible materials.</li> <li>When handling, DO NOT eat, drink or smoke.</li> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with soap and water after handling.</li> <li>Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> <li>Protect containers against physical damage and check regularly for leaks.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

# Conditions for safe storage, including any incompatibilities

Suitable container	Vial. <ul> <li>Polyethylene or polypropylene container.</li> <li>Packing as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	<ul> <li>Avoid strong acids, bases.</li> <li>Avoid reaction with oxidising agents</li> </ul>

# **SECTION 8 Exposure controls / personal protection**

#### **Control parameters**

- Occupational Exposure Limits (OEL)
- INGREDIENT DATA
- Not Available

#### Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
D-Gluconic Acid Analysis Kit - Vial 4	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
D-Gluconic Acid Analysis Kit - Vial 4	Not Available		Not Available	

#### MATERIAL DATA

Exposure	controls
----------	----------

	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Appropriate engineering	The basic types of engineering controls are:
controls	Process controls which involve changing the way a job activity or process is done to reduce the risk.
	Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically
	"adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a

	Employers may need to use multiple types of controls to pre-	emical or contaminant in use. vent employee overexposure.	
	General exhaust is adequate under normal operating conditi essential to obtain adequate protection. Provide adequate ve workplace possess varying "escape" velocities which, in turn remove the contaminant.	entilation in warehouse or closed storage areas. Air contamin	nants generated in the
	Type of Contaminant:		Air Speed:
	solvent, vapours, degreasing etc., evaporating from tank (i	n still air)	0.25-0.5 m/s (50-100 f/min)
	aerosols, fumes from pouring operations, intermittent cont drift, plating acid fumes, pickling (released at low velocity i		0.5-1 m/s (100-200 f/min.)
	direct spray, spray painting in shallow booths, drum filling, generation into zone of rapid air motion)	conveyer loading, crusher dusts, gas discharge (active	1-2.5 m/s (200-500 f/min)
	grinding, abrasive blasting, tumbling, high speed wheel ge very high rapid air motion).	nerated dusts (released at high initial velocity into zone of	2.5-10 m/s (500-2000 f/min.)
	Within each range the appropriate value depends on:		
	Lower end of the range	Upper end of the range	
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	
	2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity	
	3: Intermittent, low production.	3: High production, heavy use	
	4: Large hood or large air mass in motion	4: Small hood - local control only	
	with the square of distance from the extraction point (in simp accordingly, after reference to distance from the contaminatii 1-2 m/s (200-400 f/min.) for extraction of solvents generated considerations, producing performance deficits within the ex factors of 10 or more when extraction systems are installed of	ng source. The air velocity at the extraction fan, for example in a tank 2 meters distant from the extraction point. Other m traction apparatus, make it essential that theoretical air veloc	buld be adjusted, , should be a minimum c nechanical
Personal protection	with the square of distance from the extraction point (in simp accordingly, after reference to distance from the contaminatii 1-2 m/s (200-400 f/min.) for extraction of solvents generated considerations, producing performance deficits within the ex	le cases). Therefore the air speed at the extraction point sho ng source. The air velocity at the extraction fan, for example in a tank 2 meters distant from the extraction point. Other m traction apparatus, make it essential that theoretical air veloc	buld be adjusted, , should be a minimum c nechanical
Personal protection	<ul> <li>with the square of distance from the extraction point (in simp accordingly, after reference to distance from the contamination of 200-400 f/min.) for extraction of solvents generated considerations, producing performance deficits within the extractors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extractions or systems are installed or factors of 10 or more when extractions or systems are installed or factors of 10 or more when extractions or systems are installed or factors of 10 or more when extractions or systems are installed or factors of 10 or more when extractions or systems are installed or factors of 10 or more when extractions or use, should be called or and adsorption for the class of chemicals in use and an their removal and suitable equipment should be readily a remove contact lens as soon as practicable. Lens should</li> </ul>	le cases). Therefore the air speed at the extraction point sho ng source. The air velocity at the extraction fan, for example in a tank 2 meters distant from the extraction point. Other m traction apparatus, make it essential that theoretical air veloc	ould be adjusted, , should be a minimum o lechanical cities are multiplied by y document, describing iew of lens absorption I should be trained in ation immediately and ens should be removed in
	<ul> <li>with the square of distance from the extraction point (in simp accordingly, after reference to distance from the contamination 1-2 m/s (200-400 f/min.) for extraction of solvents generated considerations, producing performance deficits within the extractors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extractions or systems are installed or factors of 10 or more when extractions or systems are installed or factors of 10 or more when extractions or systems are installed or factors of 10 or more when extractions or systems are installed or factors of 10 or more when extractions or systems are installed or factors of 10 or more when extractions or systems are installed or factors of 10 or more when extractions or systems are installed or factors of the system are installed or factors of the class of chemicals in use and an their removal and suitable equipment should be readily a remove contact lens as soon as practicable. Lens should a clean environment only after workers have washed has a clean environment only after workers have washed has a clean environment only after workers have washed has a special system are installed or factors and an anter the environment only after workers have washed has a special system are installed or factors and and anter the environment only after workers have washed has a special system.</li> </ul>	le cases). Therefore the air speed at the extraction point sho ng source. The air velocity at the extraction fan, for example in a tank 2 meters distant from the extraction point. Other m traction apparatus, make it essential that theoretical air veloc or used. lenses may absorb and concentrate irritants. A written policy reated for each workplace or task. This should include a rev account of injury experience. Medical and first-aid personnel available. In the event of chemical exposure, begin eye irriga d be removed at the first signs of eye redness or irritation - le	ould be adjusted, , should be a minimum d lechanical cities are multiplied by y document, describing iew of lens absorption I should be trained in ation immediately and ens should be removed i
Eye and face protection	<ul> <li>with the square of distance from the extraction point (in simp accordingly, after reference to distance from the contamination 1-2 m/s (200-400 f/min.) for extraction of solvents generated considerations, producing performance deficits within the extractors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extractions or systems are installed or factors of 10 or more when extractions or use, should be called and assorption for the class of chemicals in use and an their removal and suitable equipment should be readily a remove contact lens as soon as practicable. Lens should a clean environment only after workers have washed ha national equivalent]</li> <li>See Hand protection below</li> <li>Wear chemical protective gloves, e.g. PVC.</li> <li>Wear safety footwear or safety gumboots, e.g. Rubber NOTE:</li> </ul>	le cases). Therefore the air speed at the extraction point sho ng source. The air velocity at the extraction fan, for example in a tank 2 meters distant from the extraction point. Other m traction apparatus, make it essential that theoretical air veloc or used. lenses may absorb and concentrate irritants. A written policy reated for each workplace or task. This should include a revi account of injury experience. Medical and first-aid personnel available. In the event of chemical exposure, begin eye irriga d be removed at the first signs of eye redness or irritation - le nds thoroughly. [CDC NIOSH Current Intelligence Bulletin 55 sed individuals. Care must be taken, when removing gloves	y document, describing iew of lens absorption I should be removed in sition immediately and ens should be removed in 9], [AS/NZS 1336 or
Eye and face protection	<ul> <li>with the square of distance from the extraction point (in simp accordingly, after reference to distance from the contamination 1-2 m/s (200-400 f/min.) for extraction of solvents generated considerations, producing performance deficits within the extractors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extraction systems are installed or factors of 10 or more when extractions or uses installed or factors of 10 or more when extractions on uses in use and an their removal and suitable equipment should be readily a remove contact lens as soon as practicable. Lens should a clean environment only after workers have washed ha national equivalent]</li> <li>See Hand protection below</li> <li>Wear chemical protective gloves, e.g. PVC.</li> <li>Wear safety footwear or safety gumboots, e.g. Rubber NOTE:</li> <li>The material may produce skin sensitisation in predispore equipment, to avoid all possible skin contact.</li> </ul>	le cases). Therefore the air speed at the extraction point sho ng source. The air velocity at the extraction fan, for example in a tank 2 meters distant from the extraction point. Other m traction apparatus, make it essential that theoretical air veloc or used. lenses may absorb and concentrate irritants. A written policy reated for each workplace or task. This should include a revi account of injury experience. Medical and first-aid personnel available. In the event of chemical exposure, begin eye irriga d be removed at the first signs of eye redness or irritation - le nds thoroughly. [CDC NIOSH Current Intelligence Bulletin 55 sed individuals. Care must be taken, when removing gloves	puld be adjusted, , should be a minimum o lechanical cities are multiplied by y document, describing iew of lens absorption I should be trained in attion immediately and ens should be removed ir 9], [AS/NZS 1336 or

### **Respiratory protection**

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

### **SECTION 9** Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Liquid; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available

Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	6	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (Not Available%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

# Information on toxicological effects

Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. Limited evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a significant number of individuals at a greater frequency than would be expected from the response of a normal population. Pulmonary sensitisation, resulting in hyperactive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching Significant symptoms of exposure may persist for extended periods, even after exposure ceases. Symptoms can be activated by a variety of nonspecific environmental stimuli such as automobile exhaust, perfumes and passive smoking. There exists limited evidence that shows that skin contact with the material is capable either of inducing a sensitisation reaction in a significant number of individuals, and/or of producing positive response in experimental animals.

D-Gluconic Acid Analysis Kit -	ΤΟΧΙCITY	IRRITATION	
Vial 4	Not Available	Not Available	
Legend:	1. Value obtained from Europe ECHA Registered Subst specified data extracted from RTECS - Register of Toxic		ined from manufacturer's SDS. Unless otherwise
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legena:

### D-Gluconic Acid Analysis Kit - Vial 4

- Data eitner not available or does not till the criteria for classification

✔ – Data available to make classification

### SECTION 12 Ecological information

Toxicity					
	Endpoint	Test Duration (hr)	Species	Value	Source
D-Gluconic Acid Analysis Kit - Vial 4	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Ecotox databa	n 1. IUCLID Toxicity Data 2. Europe ECHA Register ase - Aquatic Toxicity Data 5. ECETOC Aquatic Haza ation Data 8. Vendor Data			

#### DO NOT discharge into sewer or waterways.

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients
ioaccumulative pote	ential	
ioaccumulative pote		
ioaccumulative pote	Bioaccumulation No Data available for all ingredients	

Mobility in soil	
Ingredient	Mobility
	No Data available for all ingredients

### SECTION 13 Disposal considerations

#### Waste treatment methods

Product / Packaging disposal <ul> <li>Recycle wherever possible or consult manufacturer for recycling options.</li> <li>Consult State Land Waste Management Authority for disposal.</li> <li>Bury residue in an authorised landfill.</li> <li>Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul>
---

### **SECTION 14 Transport information**

Labels Required		
Marine Pollutant	NO	
HAZCHEM	Not Applicable	

### Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

### Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Ship Type

Product name	Group	
Transport in bulk in accordance with the ICG Code		

#### Product name

### **SECTION 15 Regulatory information**

### Safety, health and environmental regulations / legislation specific for the substance or mixture

#### **National Inventory Status**

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Not Available	
Canada - DSL	Not Available	
Canada - NDSL	Not Available	
China - IECSC	Not Available	
Europe - EINEC / ELINCS / NLP	Not Available	
Japan - ENCS	Not Available	

National Inventory	Status		
Korea - KECI	Not Available		
New Zealand - NZIoC	Not Available		
Philippines - PICCS	Not Available		
USA - TSCA	Not Available		
Taiwan - TCSI	Not Available		
Mexico - INSQ	Not Available		
Vietnam - NCI	Not Available		
Russia - FBEPH	Not Available		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

### **SECTION 16 Other information**

Revision Date	11/01/2019
Initial Date	08/22/2012

#### **SDS Version Summary**

Version	Date of Update	Sections Updated
2.1	08/22/2012	Fire Fighter (fire/explosion hazard), Fire Fighter (fire incompatibility), Storage (storage incompatibility), Supplier Information
4.1	11/01/2019	One-off system update. NOTE: This may or may not change the GHS classification

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.